

## A thermal boundary control method for a flexible thin disk rotating over critical and supercritical speeds

Article (Accepted Version)

Pei, Yong-Chen, Chatwin, Chris, He, Ling and Li, Wen-Zuo (2017) A thermal boundary control method for a flexible thin disk rotating over critical and supercritical speeds. *Meccanica*, 52 (1). pp. 383-401. ISSN 0025-6455

This version is available from Sussex Research Online: <http://sro.sussex.ac.uk/id/eprint/60327/>

This document is made available in accordance with publisher policies and may differ from the published version or from the version of record. If you wish to cite this item you are advised to consult the publisher's version. Please see the URL above for details on accessing the published version.

### **Copyright and reuse:**

Sussex Research Online is a digital repository of the research output of the University.

Copyright and all moral rights to the version of the paper presented here belong to the individual author(s) and/or other copyright owners. To the extent reasonable and practicable, the material made available in SRO has been checked for eligibility before being made available.

Copies of full text items generally can be reproduced, displayed or performed and given to third parties in any format or medium for personal research or study, educational, or not-for-profit purposes without prior permission or charge, provided that the authors, title and full bibliographic details are credited, a hyperlink and/or URL is given for the original metadata page and the content is not changed in any way.

**Table 1** Numerical model validation using the natural frequency for a free rotating disk

Parameters	Disk mode	Current work (Hz)	ANSYS Workbench (Hz)
Disk rotating speed $\Omega=0$ rpm	(0,0)	34.0345	33.798
	(0,1)	50.5412	50.412
	(0,2)	109.7484	109.76
	(0,3)	207.2632	207.18
	(0,4)	336.1603	335.87
Shaft temperature increment $\theta_D=20$ K	(1,0)	373.3374	373.07
	(1,1)	410.6060	410.12
	(0,5)	494.7116	494.11
Disk rotating speed $\Omega=6000$ rpm	(1,2)	531.5171	530.62
	(0,0)	55.4631	55.054
	(0,1)	113.6046	113.39
	(0,2)	213.0075	213.07
	(0,3)	331.9636	331.99
Shaft temperature increment $\theta_D=60$ K	(1,0)	400.9092	400.36
	(1,1)	452.7148	452.13
	(0,4)	472.9953	472.85
	(1,2)	604.6028	603.31
	(0,5)	639.0490	638.61